



T8 LED Retrofit

FEATURES

- Full glass housing. No distortion, no yellowing and no embrittling. Great stability.
- Compatible with most electronic instant start, programmed start and emergency T8 ballast
- Plug-n-Play
- Beam angle: 230°
- R9: 20
- 5 year warranty
- For covered use only – damp rated
- Shatter-proof available with NSF certificate

DIRECT REPLACEMENT
NO WIRING

(BALLAST BYPASS
MODELS AVAILABLE TOO)



WORKS WITH SHUNTED &
NON-SHUNTED CONNECTORS



MODEL	LUMENS	REF. POWER (W)	CRU	CAP	RATED LIFE (hours)
T8-2ft-1150lm-09W-DR ¹	1150	9.0	83	G13	50,000
T8-3ft-1450lm-11W-DR	1450	11.0	83	G13	50,000
T8-4ft-1800lm-12W-DR ¹	1800	12.0	83	G13	50,000
T8-3ft-1800lm-14W-DR ¹	1800	14.0	83	G13	50,000
T8-4ft-1800lm-15W-DR ¹	1800	15.0	83	G13	50,000
T8-4ft-2200lm-16W-DR ¹	2200	16.0	83	G13	50,000
T8-4ft-2200lm-17W-DR ¹	2200	17.0	83	G13	50,000
T8-4ft-2200lm-19W-DR ¹	2200	19.0	83	G13	50,000
T8-5ft-3000lm-23W-DR	3000	23.0	83	G13	50,000
T8-5ft-3600lm-24W-DR ¹	3500	24.0	83	Fa8	50,000
T8-3ft-4400lm-33W-DR ²	4400	33.0	83	Fa8	50,000
T8-3ft-5500lm-42W-DR ²	5500	42.0	83	R17d	50,000

¹ DLC Listed

² Shatter-Proof Only